

## SINTALIZ 7530

### CHEMICAL NATURE

: Mixture of oils, wax and modified silicones.

### APPLICATIONS

: Release agent for double density PU/PU safety boots.

### BENEFITS

- Stable under operation conditions.
- Excellent release power.
- Provides semi-matte surface finish.
- Odorless.
- Not yellowing.

### TYPICAL PROPERTIES

#### Appearance

: Hazy, flowing liquid

#### Active Content, %

: 24-26

#### Viscosity, 20°C DIN 4, sec

: 12-15

#### Density, 20°C, g/cm<sup>3</sup>

: 0,82 ± 0,02

#### Solubility

: Insoluble in water, soluble in chlorinated solvents and aliphatic and aromatic hydrocarbons

### USE

Application with air spray gun.

The spray rate is adjusted between 10-30g/min depending on the mold properties.

Recommended parameters:

Nozzle orifice: 0.3 mm

Pressure to be applied to the silicone tank: 0,5-0,8 bar

Pressure to be applied to the spray gun: 1,0 bar

Note: The application rate should be adjusted for optimal consumption.

### STORAGE

: Shelf life of at least 12 month under standart storage conditions in original packaging.

### PACKING

: 50 kg and 200 kg metal drums.

### SAFETY

: For detailed information please refer to the safety data sheet.

This information is given to the best of our knowledge. No liabilities can be derived from this fact for individual cases. For further information, please contact to TEKNİK KİMYA DONATIM MAKİNE ENERJİ SAN. VE TİC. A.Ş. Technical service.